

# Carbide Cutters - Orange Band

For use on Stainless Steel, Tough Metal, Anodised Aluminium etc.

1 of 2

## Taper Shank


### Standard Engraving Cutter



### Rigid Blade Slotting Cutter




### Heavy Duty Engraving Cutter



Description	Tip Dia.	Shank	Carbide Tipped	Single ended	Slotting Cutter	Code	Price (£)
Standard Engraving Cutter	0.140"	Taper	●	●		OT 140	11.25
Rigid Blade Slotting Cutter	0.140"	Taper	●	●	●	OTS 140	14.00
Heavy Duty Engraving Cutter	0.187"	Taper	●	●		OT 187	14.00
Heavy Duty Engraving Cutter	0.250"	Taper	●	●		OT 250	14.60

## Straight Shank



SOLID CARBIDE CUTTERS

Tip Dia

Tip Dia.	Shank Dia.	Length	Carbide Tipped	Solid Carbide	Single ended	Double Ended	Slotting Cutter	Code	Price (£)
0.125"	1/8"	1"		●	●			OS 125	7.50
0.125"	1/8"	2"		●	●			OJ 125	10.40
0.125"	1/8"	2"		●		●		OJ 125 DE	11.60
0.125"	1/8"	4"		●	●			OG 125	11.40
0.125"	1/8"	4 1/2"		●	●			OW 125	12.60
0.125"	1/8"	4 1/2"		●	●		●	OWS125	16.40
0.125"	1/8"	5"		●	●			OW125L	13.80
0.140"	11/64"	6 1/2"	●		●			OG 1164	12.10
0.140"	11/64"	200mm	●		●			OG1164200	15.50
0.140"	11/64"	6 1/2"	●		●		●	OGS1164	15.70
0.172"	11/64"	6 1/2"		●	●		●	OGS1164S	22.70
0.172"	11/64"	6 1/2"		●	●			OG 1164S	19.75
0.250"	1/4"	28mm		●	●			OM250SE	14.80
0.140"	1/4"	2"	●		●			OJ 140	8.50
0.140"	1/4"	2"	●		●		●	OJS 140	11.25
0.187"	1/4"	2"	●		●			OJ187	11.50
0.250"	1/4"	2"		●	●			OJ 250 SE	13.80
0.250"	1/4"	2"		●		●		OJ 250 DE	15.70
0.140"	1/4"	3"	●		●			OS 140	9.00
0.140"	1/4"	3"	●		●		●	OSS 140	12.40
0.187"	1/4"	3"	●		●			OS 187	11.75
0.250"	1/4"	3"		●	●			(30mm Blade) OS250SE30B	25.30
0.250"	1/4"	3"		●	●			OS250SE65	17.00
0.250"	1/4"	3"		●	●			OS 250 SE	17.00
0.250"	1/4"	3"		●		●		OS 250 DE	18.80
0.140"	1/4"	5"	●		●			OC 140	11.25
0.140"	1/4"	5"	●				●	OCS140	14.55

# Carbide Cutters - Orange Band

For use on Stainless Steel, Tough Metal, Anodised Aluminium etc.

2of2

## Straight Shank - Continued

Tip Dia.	Shank Dia.	Length	Carbide Tipped	Solid Carbide	Single ended	Double Ended	Slotting Cutter	Code	Price (£)
0.187"	1/4"	5"	●		●			OC 187	13.45
0.250"	1/4"	5"		●	●			OC 250	21.50
0.140"	1/4"	6 1/2"	●		●			OG 140	12.10
0.140"	1/4"	6 1/2"	●		●		●	OGS 140	15.25
0.188"	1/4"	6 1/2"	●		●			OG 187	14.60
0.250"	1/4"	6 1/2"		●	●			OG 250	23.90
0.250"	3/8"	3"	●		●			OS 250 38	13.45
0.140"	3/8"	5"	●		●			OS 140 38L	12.90
0.250"	3/8"	5"	●		●			OS 250 38L	14.60
0.375"	3/8"	2 1/4"		●	●			OS 375	27.50
3mm	3mm	30mm		●	●			OK 3M	7.50
3mm	3mm	35mm		●	●			OS3M35DE	13.75
3mm	3mm	50mm		●	●			OJ3MSE	10.40
3mm	3mm	50mm		●		●		OJ3MDE	11.60
4mm	4mm	30mm		●	●			OS4M30	11.60
4mm	4mm	35mm				●		OS4M35DE	15.90
4mm	4mm	45mm		●	●			OV4M45	14.80
3.5mm	4mm	62mm	●		●			OP 140 4M	11.25
3.5mm	4mm	120mm	●		●			OH 140 4M	11.55
3.5mm	6mm	165mm	●	●	●		●	OHS1406M	15.25
4mm	4mm	60mm		●	●			OH4M60	16.40
4mm	4mm	60mm		●		●		OH4M60DE	20.10
4mm	4mm	120mm		●	●			OH 4M	17.20
6mm	6mm			●	●			OM6M	14.80
6mm	6mm	45mm		●	●			OK 6M	13.80
3.5mm	6mm	50mm	●		●			OJ 140 6M	8.50
3.5mm	6mm	50mm	●		●		●	OJS1406M	11.25
6mm	6mm	50mm		●	●			OJ6MSE	13.80
6mm	6mm	50mm		●		●		OJ6MDE	15.70
3.5mm	6mm	65mm	●					OS1406M-65	8.30
3.5mm	6mm	75mm	●		●			OS 140 6M	9.00
3.5mm	6mm	75mm	●		●		●	OSS 140 6M	12.40
4.7mm	6mm	75mm	●		●			OS 187 6M	11.75
6mm	6mm	75mm		●	●			OS 6M SE	17.00
6mm	6mm	75mm		●		●		OS 6M DE	18.80
3.5mm	6mm	165mm	●		●			OH 140 6M	12.10
4.7mm	6mm	165mm	●		●			OH 187 6M	14.60
6mm	6mm	165mm		●	●			OH 6M	23.90
6.3mm	10mm	75mm	●		●			OS 250 10M	13.45
10mm	10mm	60mm		●	●			OS 10M	27.50

## Cutter Grinding

Description	Code	Price (£)
Ground Parallel	CG-PA	1.60
Any Angle	CG-AN	1.60
Back to Axis	CG-CBA	3.80
Ball Ended	CG-BE	4.00
1/4 Ground		3.80