



pantograph services

Incorporating Newing-Hall Ltd and Riggs Engraving Services Ltd

SALES & SERVICE TO THE ENGRAVING & SIGN TRADE

UNIT 8d, FELNEX CLOSE, CROSS GREEN INDUSTRIAL PARK, LEEDS, LS9 0SR

TELEPHONE: (0113) 249 6161 FAX: (0113) 249 7033

VAT REGISTRATION No GB 332369855

[E-mail: sales@pantograph.co.uk](mailto:sales@pantograph.co.uk) www.pantograph.co.uk

Filling Paint

Product Composition:

A blend of Nitro-cellulose, synthetic resins and other plasticizers, suitably pigmented for colour and dissolved in a mixture of Alcohol, Ketone, Glycol Ether and aromatic Hydrocarbon solvents.

Regulations:

The storage and use of Filling Paint is Governed by:

(1)The Petroleum (Consolidation) Act 1928

(2)The Highly Flammable Liquid and Liquefied Petroleum Gases Regulations 1972

Protective Measures Data

Personal:

Inhalation: Remove to fresh air, and keep patient warm. Give nothing by mouth.

Eye Contact: Irrigate copiously with clean fresh water for at least ten minutes, holding the eyelids apart.

Skin Contact: Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleaner. Do not use solvents or thinners.

Ingestion: In case of accidental ingestion, obtain immediate Medical attention. Do Not Induce Vomiting.

Storage:

Store in accordance with the conditions of Licence necessary under the Petroleum (Consolidation) Act 1928.

Fire Hazard:

These products are highly flammable with a flash point (Closed Cup) below 22°. To prevent the creation of a flammable concentration of vapour in the air, good natural ventilation and, if necessary, local exhaust ventilation should be provided. Additionally, the product should only be used in areas from which all naked lights and other sources of ignition, including unprotected electrical equipment have been excluded

Fire Fighting:

Fire will produce dense black smoke containing harmful products of combustion. Use foam or dry powder extinguishing agents. Cool containers exposed to fire with water

Spillage:

Contain and collect spillage with non-combustible absorbent materials, eg Sand or Earth. Do not allow to enter drains. Exclude sources of ignition and ventilate areas.

Waste Disposal:

Waste materials must be treated as a fire hazard and disposed of in accordance with the Control of Pollution Act 1974